

MANUFACTURING CO., LLC.

P.O. Box 620 | 602 Eagan Road | Black Rock, Arkansas 72415 P 870.878.6805 | F 870.878.6280 | www.eaganmfg.com

E300 D00RS

Our E300 door has all the necessary ingredients to make a very durable yet economical door for agricultural and post-frame applications.

Door Core Specs

- 1-5/8" capped edge polyurethane insulated door pane—R-11 insulation value
- Pre-hung
- · Vinyl v and bulb seal
- Door skins are pre-painted white and available in different steel and aluminum options

Door Skins Available

Door Width	.010 Steel	.014 Steel	.019 Aluminum
36"	X		X
48"		X	X

Door Jamb

- · 3-1/2" aluminum jamb
- · Jamb is available in mill or pre-painted white finish
- Stainless steel lubricated hinges
- · Vinyl v and bulb seal
- · Adjustable strike plate

Standard Door Sizes

32	2 x	80	
3(6 X	72	
3(6 X	80	
48	3 x	72	
48	3 x	80	

*other smaller and custom sizes available

Rough Opening

Add 1-3/4" to width and 2" to height



Stainless Steel Strike Plate



Low Profile Threshold



Stainless steel lubricated hinge for strength and durablity

Options/Accessories

Mounting Flange



Optional for flush mount installation



Optional for J Channel installation

Deadbolts/Prep for Deadbolts



Snap Cap



Chains



Locksets



20 x 24 one lite window



available either insulated or non-insulated

22 x 36 9-lite window



available either insulated or non-insulated