

EAGAN

MANUFACTURING CO., LLC.

P.O. Box 620 | 602 Eagan Road | Black Rock, Arkansas 72415
P 870.878.6805 | F 870.878.6280 | www.eaganmfg.com



Folding Doors with **STURDY DRIVE**® Hoist System

- **STURDY DRIVE**® Hoist System has many improvements with no cost increase
 - o Faster install
 - o More efficient operation
 - o Revolutionary door kicker system (patent pending) starts the opening process as soon as the door is unlatched
 - o Allows for easy access for operation in instances of close proximity to equipment (e.g., fans, cool cells, entrance doors, etc.)
- Fully integrated seal system eliminates seal installation
 - o Offers improved sealing performance
- Polyurethane foam injected door panels with an R-7 insulation value
- Skin on the inside of the door can be black to aid in room darkening
- Chain guide to keep chain centered on hand wheel
- Door comes complete with all necessary hardware
- Quality product that will last for years to come



Specifications

- **STURDY DRIVE**® Hoist System
- Epdm rubber seal system
- 2.5 lb. density polyurethane foam
- .010 galvanized stucco embossed steel outer door skin
- .019 smooth aluminum or fiberglass inner door skin
- Snap on H-channel meeting rail
- Upper continuous hinge is made of 1/4" wall aluminum extrusion
- 1/4" stainless steel continuous hinge
- (6) 3" X 4" hinge tabs
- Center continuous hinge is 1/4" stainless steel pin piano hinge
- Hinge is sealed with a 3/4" x 1/2" foam seal
- (2) 3" x 1" nylon rollers with 1/2" stainless steel axles
- Galvanized upper assembly cover